




DONALDSON DELIVERS

Oil filter cart for off-line filtration



The Donaldson oil filter cart X770793 provides a convenient portable mode of off-line filtration, flushing and fluid transfer. Use it with your in-plant machinery and mobile equipment to achieve and maintain proper ISO cleanliness levels.

In-series pressure filter can provide fine particle removal and a water absorbing element to obtain particulate and water removal. The powerful 50 lpm pump provides efficient fluid transfer and filtration.




The Donaldson oil filter cart is designed with performance, convenience and safety in mind. Its value added features make it the best choice to protect your machinery and equipment from breakdowns caused by contamination and water.

Oil filter cart features

Features	Benefits
Rugged and durable frame	Enables long service life
High-efficiency media grades	Cost effective filtration
Two pressure filters	Two-stage filtration – Fine Particulate and/or Water
Safety relief valve	Prevents over pressurizing and damage to pump, hoses and filters
Overload protected switch	Prevents motor/pump from overheating

Applications

Filter new fluid	New fluids are usually above the recommended ISO cleanliness level.
Off-line filtration	Filter cart can be used to supplement existing filtration
Transferring fluid	Fluid is transferred from a storage container (tote, drum, tank, etc.) to a machine's reservoir
Water removal	Using Donaldson water removal elements can help remove free water from the system
Flushing after repairs and rebuilds	After machines are serviced or repaired they need to be flushed thoroughly before they are returned to service
Flushing during equipment commissioning	New machines have original fabrication debris and dirt that has ingressed during transport and storage



Differential pressure indicators


- Lets you know when to change elements

Two pressure filters mounted in series

- Allows for particulate/water removal or coarse/fine particle removal

Removable angled drip tray

- Easy clean up, fluid will not leak out when tipped back



Dual electrical indicators with flashing on the dashboard + manometer for pump

- (to monitor filter performance and give servicing instructions)

Motor mounted inside

- Better balance
- Fluid will not drip on motor when changing filters
- Main pump protected by a cover

Overload protected switch


- Protects motor and pump from overheating

Integrated safety relief valve

- Protects against over pressurizing

Optional

- Anti-drain suction valve



Oil filter cart specifications

Supply	220 V @ 50/60 Hz
Electric motor	Built-in thermal lockout
Electric cable	5 m
Maximum fluid viscosity	300 cSt
Flow rate	50 lpm
Maximum Pressure	5 bar (internal bypass)
Indicators	Dual electrical indicators with flashing on the dashboard + manometer for pump pressure
Suction hose	3 m
Discharge hose	4 m
Dirt filtration	P766847 ($\beta_{7\mu m(c)} > 1000$) *
Water adsorption	P766849 (95% Water removal efficiency) *
Optional	Suction anti-drain valve

* Different filter configurations are possible.



Donaldson Europe b.v.b.a.
Interleuvenlaan 1
3001 Leuven
Belgium

Engine-europe@donaldson.com
www.donaldson.com

Europe +32-16-38-3811
North America 800-374-1374
Mexico +52-449-910-6150
Latin Am. & Carib. +52-449-910-6150
Brazil +55-11-2119-1604
South Africa +27-11-997-6000

South East Asia 65-6311-7373
Greater China 852-2405-8388
Japan 81-42-540-4112
Australia 61-02-4350-2033
India +91-124-2290060

Brochure No. F111380 (09/13)
© 2013 Donaldson Company, Inc.
Donaldson Company, Inc. reserves the right to change or discontinue any model or specification at any time and without notice.